

## SNATCH BLOCKS

- Fittings are painted yellow for quick recognition
- Designed for intermittent use with low line speed
- Ultimate load 4 times working load limit (WLL)
- Bronze bush with grease nipple



Model No.	For Rope Diameter"	Sheave Diameter"	Working Load Limit	Price /Each
<b>HOOK &amp; LATCH</b>				
LU897	3/8	3	4000 lbs. (2 tons)	
LU898	1/2	4-1/2	8000 lbs. (4 tons)	
LU899	3/4	6	16000 lbs. (8 tons)	
LU900	3/4	8	16000 lbs. (8 tons)	
LU901	3/4	10	16000 lbs. (8 tons)	
LU902	1-1/8	8	30000 lbs. (15 tons)	



LU897

<b>SWIVEL SHACKLE</b>				
LU904	3/8	3	4000 lbs. (2 tons)	
LU905	1/2	4-1/2	8000 lbs. (4 tons)	
LU906	3/4	6	16000 lbs. (8 tons)	
LU907	3/4	8	16000 lbs. (8 tons)	
LU908	3/4	10	16000 lbs. (8 tons)	
LU909	5/8	14	16000 lbs. (8 tons)	
LU910	1-1/8	8	30000 lbs. (15 tons)	
LU912	1-1/8	8	40000 lbs. (20 tons)	



LU904

<b>TAILBOARD W/PIN ONLY</b>				
LU913	3/8	3	4000 lbs. (2 tons)	
LU914	1/2	4-1/2	8000 lbs. (4 tons)	
LU915	3/4	6	16000 lbs. (8 tons)	
LU916	3/4	8	16000 lbs. (8 tons)	



LU913

## SCREW PIN CHAIN SHACKLES

- Heat treated carbon steel bows, quenched and tempered with Alloy pins
- Shackle Bow Finish: Hot Dip Galvanized
- Meets the performance requirements of U.S. Fed. Spec. RR-C-271D, ASME B30.26, Type 4A, Class 2 Grade A



Model No.	Size"	Pin Diameter"	Capacity	Price /Each
LU773	3/8	7/16	2000 lbs. (1 tons)	
LU774	7/16	1/2	3000 lbs. (1.5 tons)	
LU775	1/2	5/8	4000 lbs. (2 tons)	
LU776	5/8	3/4	6500 lbs. (3.25 tons)	
LU777	3/4	7/8	9500 lbs. (4.75 tons)	
LU779	1	1-1/8	17000 lbs. (8.5 tons)	
LU781	1-1/4	1-3/8	24000 lbs. 12 tons)	
LU782	1-1/2	1-5/8	34000 lbs. (17 tons)	



LU773

## LIFTING SWIVEL HOIST RINGS

- Designed for angular lifting
- Hoist rings resist stresses that would bend or break an eyebolt
- Pivots 180° front to back and a base that swivels 360°
- Working load limit and nominal size meet ASME B 30.26 standards
- The proof load is 2 x Working load limit and Minimum Breaking Strength is 4 x Working Load Limit
- Made from grade 80 alloy steel



LU815



Model No.	Thread Size	Thread Length mm	Working Load Limit	Working Load Limit at 90° Angle	Price /Each
LU815	M8	13	1200 lbs. (0.6 tons)	600 lbs. (0.3 tons)	
LU817	M10	18	1800 lbs. (0.9 tons)	900 lbs. (0.45 tons)	
LU819	M12	20	2000 lbs. (1 tons)	1000 lbs. (0.5 tons)	
LU822	M16	30	4000 lbs. (2 tons)	2240 lbs. (1.12 tons)	
LU824	M20	30	8000 lbs. (4 tons)	4000 lbs. (2 tons)	
LU826	M24	30	12600 lbs. (6.3 tons)	6300 lbs. (3.15 tons)	
LU828	M30	35	21200 lbs. (10.6 tons)	10600 lbs. (5.3 tons)	
LU830	M36	54	23600 lbs. (11.8 tons)	23600 lbs. (11.8 tons)	
LU831	1/4"	13	1200 lbs. (0.6 tons)	606 lbs. (0.9 tons)	
LU832	5/16"	13	1320 lbs. (0.66 tons)	661 lbs. (0.33 tons)	
LU833	3/8"	18	1980 lbs. (0.99 tons)	1100 lbs. (0.55 tons)	
LU834	7/16"	18	2200 lbs. (1.1 tons)	1100 lbs. (0.55 tons)	
LU835	1/2"	20	2200 lbs. (1.1 tons)	1100 lbs. (0.55 tons)	
LU836	5/8"	20	4400 lbs. (2.2 tons)	2469 lbs. (1.23 tons)	
LU837	3/4"	30	8810 lbs. (4.4 tons)	4400 lbs. (2.2 tons)	
LU838	7/8"	30	1100 lbs. (0.55 tons)	5510 lbs. (2.755 tons)	
LU839	1"	30	13880 lbs. (6.94 tons)	6945 lbs. (3.47 tons)	
LU840	1-1/4"	50	26000 lbs. (13 tons)	17637 lbs. (8.8 tons)	

## SCREW PIN ANCHOR SHACKLES

- Heat treated carbon steel bows, quenched and tempered with Alloy pins
- Meets the performance requirements of U.S. Fed. Spec. RR-C-271D, ASME B30.26, Type 4A, Class 2 Grade B



Model No.	Size"	Pin Diameter"	Capacity	Price /Each
<b>YELLOW CHROMATE PLATED</b>				
LU729	3/8	7/16	4000 lbs. (2 tons)	
LU730	7/16	1/2	5300 lbs. (2.65 tons)	
LU731	1/2	5/8	6600 lbs. (3.3 tons)	
LU732	5/8	3/4	10000 lbs. (5 tons)	
LU733	3/4	7/8	14000 lbs. (7 tons)	
LU734	7/8	1	19000 lbs. (9.5 tons)	
LU735	1	1-1/8	25000 lbs. (12.5 tons)	
LU736	1-1/8	1-1/4	30000 lbs. (15 tons)	
LU737	1-1/4	1-3/8	36000 lbs. (18 tons)	
LU738	1-1/2	1-5/8	60000 lbs. (30 tons)	



LU729

<b>HOT DIP GALVANIZED</b>				
LU739	3/16	1/4	660 lbs. (0.33 tons)	
LU740	1/4	5/16	1000 lbs. (0.5 tons)	
LU741	5/16	3/8	1500 lbs. (0.75 tons)	
LU742	3/8	7/16	2000 lbs. (1 tons)	
LU743	7/16	1/2	3000 lbs. (1.5 tons)	
LU744	1/2	5/8	4000 lbs. (2 tons)	
LU745	5/8	3/4	6500 lbs. (3.25 tons)	
LU746	3/4	7/8	9500 lbs. (4.75 tons)	
LU747	7/8	1	13000 lbs. (6.5 tons)	
LU748	1	1-1/8	17000 lbs. (8.5 tons)	
LU749	1-1/8	1-1/4	19000 lbs. (9.5 tons)	
LU750	1-1/4	1-3/8	24000 lbs. 12 tons)	
LU751	1-1/2	1-1/2	27000 lbs. (13.5 tons)	
LU752	1-1/2	1-5/8	34000 lbs. (17 tons)	
LU753	1-3/4	2	50000 lbs (25 tons)	
LU754	2	2-1/4	70000 lbs. (35 tons)	
LU755	2-1/2	2-3/4	110000 lbs. (55 tons)	



LU739

## STAINLESS STEEL

- To be used for light duty, non-critical applications only
- Made from AISI-316 stainless steel
- Bright polished finish

Model No.	Size"	Pin Diameter"	Capacity	Price /Each
LU787	1/4	5/16	500 lbs. (0.25 tons)	
LU788	5/16	3/8	660 lbs. (0.33 tons)	
LU789	3/8	7/16	1000 lbs. (0.5 tons)	
LU791	1/2	5/8	2000 lbs. (1 tons)	
LU792	5/8	3/4	3000 lbs. (1.5 tons)	
LU793	3/4	7/8	4500 lbs. (2.25 tons)	
LU795	1	1-1/8	8000 lbs. (4 tons)	



LU787

## BOLT TYPE ANCHOR SHACKLES

- Heat treated carbon steel bows, quenched and tempered with Alloy pins
- Shackle Bow Finish: Hot Dip Galvanized
- Meets the performance requirements of U.S. Fed. Spec. RR-C-271D, ASME B30.26, Type 4A, Class 3 Grade A
- Recommended for long term service installation as well as for applications where there is the possibility that the pin can rotate under load



Model No.	Size"	Pin Diameter"	Capacity	Price /Each
LU756	1/4	5/16	1000 lbs. (0.5 tons)	
LU757	5/16	3/8	1500 lbs. (0.75 tons)	
LU758	3/8	7/16	2000 lbs. (1 tons)	
LU759	7/16	1/2	3000 lbs. (1.5 tons)	
LU760	1/2	5/8	4000 lbs. (2 tons)	
LU761	5/8	3/4	6500 lbs. (3.25 tons)	
LU762	3/4	7/8	9500 lbs. (4.75 tons)	
LU763	7/8	1	13000 lbs. (6.5 tons)	
LU764	1	1-1/8	17000 lbs. (8.5 tons)	
LU765	1-1/8	1-1/4	19000 lbs. (9.5 tons)	
LU766	1-1/4	1-3/8	24000 lbs. 12 tons)	
LU767	1-3/8	1-1/2	27000 lbs. (13.5 tons)	
LU768	1-1/2	1-5/8	34000 lbs. (17 tons)	
LU769	1-3/4	2	50000 lbs (25 tons)	
LU770	2	2-1/4	70000 lbs. (35 tons)	



LU756