

CLECO® 19 SERIES - STALL SCREWDRIVERS

- Tool weight: 1.16 lbs.
- Tool length: 5.9"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- Trigger start
- "P" handle style
- Interchangeable soft-touch grip sizes
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless

Model No. TYN249
Mfg. No. 19PTS04Q
Price/Each \$

Cleco®



CLECO® 19 SERIES - PISTOL GRIP SCREWDRIVERS W/ADJUSTABLE TORQUE SETTINGS

- Tool weight: 1.41 lbs.
- Tool length: 8.0"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Class-leading accuracy and repeatability
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- "P" handle style
- Interchangeable soft-touch grip sizes
- Trigger and Push & Trigger start
- External torque adjustment from 10 - 40 in.-lbs.
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless

Model No. TYN248
Mfg. No. 19PTA04Q
Price/Each \$

Cleco®



CLECO® RIGHT ANGLE GRINDERS

- Compact, yet powerful motor
- Reversible safety lever throttle
- Dual auxiliary handle positions
- Maximum material removal for a right angle grinder
- Streamlined all metal housing
- Performance rated @ 90 PSI / 620 kPa air pressure
- Air consumption: 15 CFM
- Air inlet: 1/2"
- No load RPM: 12 000

Cleco®



| Model No. | Mfg. No. | Wheel Size" | Spindle Size | Motor Power HP | Price /Each |
|--------------------|----------------|-------------|--------------|----------------|-------------|
| 1660 SERIES | | | | | |
| TYM371 | 1660AGL-04 | 4 | 3/8" | 1.6 | |
| TYM374 | 1660AGL-45 | 4 1/2 | 5/8" | 1.6 | |
| TYM372 | 1660AGL-05 | 5 | 5/8" | 1.6 | |
| TYM373 | 1660AGL-05-M14 | 5 | M14 | 1.6 | |
| 2260 SERIES | | | | | |
| TYM396 | 2260AGL-06 | 6 | 5/8" | 2.2 | |
| TYM397 | 2260AGL-07 | 7 | 5/8" | 2.2 | |

CLECO® CWC PREMIUM COMPOSITE SERIES - IMPACT WRENCHES

- The ultimate balance of performance, ergonomics and durability
- Composite housing with a high output motor that delivers a maximum power-to-weight ratio
- On hand push button forward/reverse with variable speed trigger, dial speed settings
- Twin hammer impact mechanism

Cleco®

| Model No. | Mfg. No. | Air Consumption CFM | Retainer Type | Drive" Per Minute | Impacts Per Minute | Free Speed RPM | Max Torque ft.-lbs. | Price /Each |
|---------------|-----------|---------------------|--------------------|-------------------|--------------------|----------------|---------------------|-------------|
| TYN508 | CWC-250QC | 2.7 | Quick Change Chuck | 1/4 | 1200 | 13000 | 50 | |
| TYN507 | CWC-250R | 2.7 | Ring | 1/4 | 1200 | 13000 | 50 | |
| TYN501 | CWC-375R | 5.3 | Ring | 3/8 | 1600 | 10000 | 450 | |
| TYN503 | CWC-375P | 5.3 | Pin | 3/8 | 1600 | 10000 | 450 | |
| TYN509 | CWC-500R | 5.7 | Ring | 1/2 | 1250 | 8000 | 800 | |
| TYN512 | CWC-500P | 5.7 | Pin | 1/2 | 1250 | 8000 | 800 | |
| TYN511 | CWC-500RE | 5.7 | Ring* | 1/2 | 1250 | 8000 | 800 | |
| TYN514 | CWC-500PE | 5.7 | Pin* | 1/2 | 1250 | 8000 | 800 | |
| TYN505 | CWC-750P | 9.7 | Pin | 3/4 | 1200 | 6500 | 1400 | |

*Extended anvil



TYN507

CLECO® CWM PREMIUM METAL SERIES - IMPACT WRENCHES

- Engineered for heavy duty applications in the most demanding environment
- Rugged all-metal construction
- Withstands heavy abuse with twin impact mechanism
- Large lever forward/reverse and speed settings with variable speed trigger
- Soft touch grip protects against slip, temperature and vibration

Cleco®

| Model No. | Mfg. No. | Air Consumption CFM | Retainer Type | Drive" Per Minute | Impacts Per Minute | Free Speed RPM | Max Torque ft.-lbs. | Price /Each |
|---------------|----------|---------------------|---------------|-------------------|--------------------|----------------|---------------------|-------------|
| TYN496 | CWM-375R | 3.8 | Ring | 3/8 | 1400 | 12000 | 340 | |
| TYN497 | CWM-375P | 3.8 | Pin | 3/8 | 1400 | 12000 | 340 | |
| TYN499 | CWM-500R | 5.6 | Ring | 1/2 | 1200 | 9000 | 850 | |
| TYN500 | CWM-500P | 5.6 | Pin | 1/2 | 1200 | 9000 | 850 | |
| TYN498 | CWM-750P | 7.6 | Pin | 3/4 | 1200 | 6000 | 1350 | |



TYN499

DOTCO® 15LF SERIES - RIGHT ANGLE DRILLS

- Tool weight: 1.7 lbs.
- Tool length: 11.0"
- Motor power: 0.4 HP (0.30 kW)
- Engineered for heavy duty applications in the most demanding environment
- Reinforced angle head for added durability
- Comfortable and ergonomic handle
- Performance rated @ 90 PSI / 620 kPa air pressure
- Air consumption: 22 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- No load RPM: 3700

Model No. TYM161
Mfg. No. 15LF281-52
Price/Each \$

DOTCO®

