# FALL PROTECTION

#### SHOCKWAVE<sup>™</sup> 2 LANYARDS

- · Tubular core style lanyards uniquely designed to expand and contract in reaction to a workers movements
- Stays out of your way when not in use, avoiding trips and snags

SEB869

Harness

Connection

Snap Hook

Snap Hook

Snap Hook

PROTM PACK SHOCK ABSORBING LANYARDS

Anchorage

Connections

Snap Hook

Snap Hooks

Snap Hook

Built in impact indicator provides visual evidence if the lanyard has been involved in a fall

No. of

Legs

One

Two

NOMEX/KEVLAR ARC FLASH RATED LANYARDS

0ne

Length: 6

Fall Protection

Mfg.

No

STANDARD LANYARDS

12443060

1242450C

1244610C

Model

SFB868

SEB869

SEP841

No

Certification(s): CSA Standard Z259.11

### EZ-STOP<sup>™</sup> SHOCK ABSORBING LANYARDS

- Features the lightest, smallest, and strongest shock absorber in
- the world; 66% smaller and 40% lighter than previous EZ-Stop™ models
- Lightest and strongest rebar hooks on the market Thinnest-ever webbing using HI-10<sup>™</sup> Vectran<sup>®</sup> energy
- management material for reduced weight and bulk Vectran<sup>®</sup> is a multifilament high tenacity performance fibre spun
- from liquid crystal polymer that is five times stronger than steel
- Repel<sup>™</sup> webbing repels water to reduce the attraction of mold and dirt
- High abrasion resistance

SEB868

Price

/Each

CSA Mass Ibs.

max

253

385

253

min

133

177

133

- Excellent chemical and cut resistance .
- High impact resistance
- . High visibility accents keep you safe in low-light conditions • Protected labels for durability and longevity
- Rugged and durable soft shock absorber cover is designed to last
- Certification(s): CSA Standard Z259.11



Model	Mfg.		No. of	Harness	Anchorage	CSA Mass lbs.		Price
No.	No.	Length'	Legs	Connection	Connections	min.	max.	/Each
SEJ418	1246012C	3	One	Snap Hook	Snap Hook	122	308	
SEJ419	1246017C	4	0ne	Snap Hook	Snap Hook	122	308	
SEJ421	1246102C	6	0ne	Snap Hook	Rebar Hook	122	308	
SEJ422	1246022C	6	Two	Snap Hook	Snap Hooks	122	308	
SEJ423	1246024C	6	Two	Snap Hook	Rebar Hooks	122	308	

#### Pack-type shock absorber limits fall arrest forces to 900 lbs. for added safety Durable 1" polyester web construction Durable alloy steel, zinc-plated hardware • Harness Connection: Snap Hook Certification(s): CSA Standard Z259.11 SFB872 SEB384 Ð PROTECTA Fall Protection

Model	Mfg.		No. of	Anchorage	CSA Mass lbs.		Price
No.	No.	Length'	Legs	Connections	min.	max.	/Each
SEB871	1341004C	4	One	Snap Hook	122	308	
SEB872	1341001C	6	One	Snap Hook	122	308	
SEB384	1340125C	6	One	Gate Hook	122	308	
SEF153	1340180C	6	Two	Gate Hooks	122	308	
SES801	1360180C	6	Two	Gate Hooks	177	418	

## WEB ADJUSTABLE POSITIONING LANYARD

- 6 ft. (1.8m) adjustable single-leg lanyard .
- Ideal for work positioning or restraint Abrasion resistant polyester webbing
- Built-in wear indicator User friendly self locking
- snap hooks at each end
- Equipped with i-Safe™



#### PRO™ PACK HOT WORK SHOCK ABSORBING LANYARD

- Lightweight user friendly design
- Fire resistant Kevlar® fiber webbing
- PVC shock pack with Kevlar<sup>®</sup> cover Energy absorbing design
- limits fall arrest forces
- User friendly self locking
- snap hooks at each end
- Impact indicator
- Harness Connection: Snap Hook
- Certification(s): CSA Standard Z259.11 .

Model No.		Length'	No. of Legs	3		Fall Protection	
	Mfg. No.			Anchorage Connections	CSA Ma min.	iss lbs. max.	Price /Each
SDP386 SDP388	1340129C 1340186C	6 4	One Two	Rebar Hook Rebar Hooks	122 122	308 308	

SDP386

SP

