

## FIXED BEAM ANCHORS

- Installs in seconds to the beam structure in any orientation
- Final tightening using a built-in adjustment handle
- Fits up to 1 1/2" thick beam flange, 2 1/2" to 12" wide

**Model No. SEE808**  
**Mfg. No. 2108406**  
**Price/Each \$**



## SLIDING BEAM ANCHOR

- Versatile size ranges to fit a variety of beams
- Replaceable wear pads
- 360-degree swiveling D-ring anchor point
- Integrated dual ratcheting system
- High-strength, lightweight steel and aluminum construction
- 5000 lb. strength and up to 420 lb. (189 kg) capacity
- Type: Temporary
- Style: I-Beam

**Model No. SGJ699**  
**Mfg. No. 2104710**  
**Price/Each \$**



## FREESTANDING COUNTERWEIGHT ANCHORS

- Freestanding system is easily placed on top of the roof surface to provide tie-off point for one worker

**Model No. SEE809**  
**Mfg. No. 7200439**  
**Price/Each \$**



## DOOR/WINDOW JAMB ANCHORS

- Fits door or window sizes ranging from 21 1/2" to 51 1/2" in width
- Non-penetrating design ensures no damage to structure
- Fast and easy installation with built-in adjustment knob – no tools or drilling are required
- Lightweight and extremely portable design

**Model No. SEJ618**  
**Mfg. No. 2100080**  
**Price/Each \$**



## LAD-SAF™ ROPE GRABS

- Mobile design automatically follows users for hands-free operation
- Detachable design can be attached or removed anywhere along lifeline
- Inertia and cam locking systems for safety and to prevent "panic-grab"
- For use on 5/8" (16 mm) polyester/polypropylene rope lifeline
- Use with 3' shock absorbing lanyard

**Model No. SEB433**  
**Mfg. No. 5000335C**  
**Price/Each \$**



## BEAM TROLLEY ANCHORAGE CONNECTORS

- Installs easily and quickly overhead with no tools necessary at ends or midpoint on beams
- Non-corrosive double-shielded wheel bearings provide smooth and effortless operation
- Trolley guards protect the wheels from damage and keep the beam ahead of the trolley clear of debris
- Provides added maneuverability, improved safety, and increased productivity
- Fits flat or tapered beam flanges 3" to 8" wide, and up to 11/16" thick

**Model No. SEJ617**  
**Mfg. No. 2103143**  
**Price/Each \$**



## COBRA™ MOBILE/MANUAL ROPE GRAB WITH LANYARD

- Mobile design automatically follows user
- Manual option allows user to fix in place
- Cam locking system for safety
- Integral 2 ft. (0.6 m) Pro™ shock absorbing lanyard
- Detachable anywhere along the lifeline
- Durable and lightweight corrosion-resistant construction
- For use with 5/8" (16 mm) diameter polyester/polypropylene blend rope lifeline
- Rope Diameter: 5/8"

**Model No. SEP896**  
**Mfg. No. AC202C-SA2**  
**Price/Each \$**



## ROPE LIFELINES

- 16 mm (5/8") diameter, polyester sheath with polypropylene core
- Tensile strength: 2540 kg (5600 lbs.)
- Zinc plated stamped steel hook
- Net weight: 5.6 lbs. (25 kg)



| Model No. | Mfg. No.   | Length' | Price /Each |
|-----------|------------|---------|-------------|
| SEB381    | SSR100-50  | 50      |             |
| SEB382    | SSR100-100 | 100     |             |