

# AIR TOOLS



## 3/8" IMPACT WRENCHES

### For general maintenance

- Twin hammer clutch
- Composite handle and magnesium clutch housing
- S2S technology allows to effortless change between forward and reverse
- Three positive power settings
- Full teasing trigger

Model No. TLV696



## 3/8" BUTTERFLY IMPACT WRENCHES

- Butterfly forward/reverse throttle
- Rocking dog clutch for smooth operations and durability
- Four positive power settings
- Easy maneuvering with 360° air inlet swivel
- Comfort and maneuverability
- Shank size: 3/8"
- Shank retainer type: Friction ring
- Working torque: 5-65 ft-lbs.
- Ideal for bench work, carburetors, ignitions, body panels, transmissions, oil pans and small engine repair

Model No. THZ806



## 3/8" IMPACT WRENCHES

### General duty for maintenance/repair.

- High torque Dyna Pact™ clutch
- Ergonomic handle for excellent balance and feel
- 1/4" (NPTF) air inlet thread
- 3/8" min. hose size

Model No. THZ944



## 1/2" IMPACT WRENCHES

### Standard duty for use in a variety of fastening operations.

- Dyna Pact™ clutch
- Built-in power regulator
- Push-through reverse mechanism

Model No. THZ946



## 1/2" IMPACT WRENCHES

### For general duty repair/maintenance and light-to-medium assembly applications.

- Twin clutch increases ultimate torque for smooth operation under heavy loading
- Oil bath clutch
- Teasing throttle

Model No. THZ948



## 3/4" IMPACT WRENCHES

### High ultimate torque for tough applications.

- Ideal for hard pull up conditions
- Push-through reverse mechanism
- Teasing throttle
- Oil bath clutch chamber
- Pin clutch
- 3/8" (NPTF) air inlet thread
- 3/8" min. hose size

Model No. THZ955



## 1" IMPACT WRENCHES

### Standard duty for use in steel erection, heavy assembly/disassembly, maintenance/repair, and construction.

- Teasing throttle
- Rocking dog clutch
- Closed-grip inside trigger
- 6" extended shank
- 1/2" (NPTF) air inlet thread
- 1/2" min. hose size

Model No. TJZ370



# Chicago Pneumatic™

Model No.	Mfg. No.	Shank Size		Shank Retainer Type	Working Torque		Maximum Torque		CFM	Overall Length		Net Weight		Price /Each
		in.	mm		ft-lbs.	Nm	ft-lbs.	Nm		in.	mm	lbs.	kg	
TLV696	CP7722	3/8	10	Friction Ring	50-300	68-407	415	563	20	6 1/2	163	2.8	1.3	
THZ806	CP772	3/8	10	Friction Ring	5-50	6.8-70	90	122	10	5 3/4	146	2	0.9	
THZ944	CP724H	3/8	10	Friction Ring	20-160	27-217	200	272	12	6	152	3.1	1.4	
THZ946	CP734H	1/2	13	Friction Ring	25-310	34-420	425	576	15	7 1/2	191	5	2.3	
THZ948	CP749	1/2	13	Friction Ring	25-330	34-450	450	610	16	7 1/2	194	5.5	2.5	
THZ955	CP772H	3/4	19	Friction Ring	150-700	200-950	1000	1360	24	9 5/8	244	10.5	4.8	
TJZ370	CP797	1	25.4	Hole for Socket Pin	150-900	200-1225	1400	1900	40	15 1/2	394	27	12.3	

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

Standard equipment: removable dead handle. **TG063:** Socket pin and retaining ring. **TG065:** adjustable and removable dead handle, socket pin and retaining ring.