

## 1/4 ARO 210 INTERCHANGE PLUGS

- Zinc plated steel construction
- Corrosion resistant
- Made to precise standards to ensure fit

### TOPRING

Model No.	Mfg. No.	NPT	Price/Each
<b>FEMALE THREAD</b>			
TA284	23.142	1/4	
<b>MALE THREAD</b>			
TA285	23.242	1/4	
TLV349	23.248	1/4 (w/thread sealant)	



TA284



TS388

Model No.	Mfg. No.	I.D."	Price/Each
<b>HOSE BARB</b>			
TG020	23.342	1/4	
TS392	23.362	3/8	

## 1/4 TRUFLATE INTERCHANGE PLUGS

- Accepts 1/4 Trufflate couplers
- Compact design
- Automatic push-to-connect design
- 250 PSI
- 24 SCFM

Model No.	Mfg. No.	NPT	Price/Each
<b>MALE THREAD</b>			
TS412	24.242	1/4	

### TOPRING



## QUIKSILVER ULTRAFLO INTERCHANGE COUPLER (E 7.8)

- Delivers high air volume with low pressure drop for better tool performance
- Corrosion resistant for long service life
- Drag guard protects against accidental disconnection
- Automatic push-to-connect operation
- Maximum 500 PSI
- 80 SCFM
- Accepts European (CEJN 320) type plugs (Ultraflo)

NPT	Model No.	Mfg. No.	Price /Each
<b>FEMALE THREAD</b>			
1/4	TS510	31.744	
3/8	TS513	31.764	
<b>MALE THREAD</b>			
1/4	TS514	31.844	
3/8	TS516	31.864	

TS510



### TOPRING

## ULTRAFLO INTERCHANGE PLUGS

- High flow for better tool performance
- Compatible with European (CEJN 320) type couplers
- Hardened steel construction

### TOPRING

Model No.	Mfg. No.	NPT	Price/Each
<b>FEMALE THREAD</b>			
TZ213	31.542	1/4	
TS506	31.562	3/8	
<b>MALE THREAD</b>			
TZ214	31.642	1/4	
TS508	31.662	3/8	



TZ213



TZ214

Model No.	Mfg. No.	I.D."	Price/Each
<b>HOSE BARB</b>			
TS519	31.962	3/8	