

# FITTINGS, COUPLINGS & CLAMPS



## 30° FREE ANGLE FITTINGS

- Prevents kinking and tangling of hoses
- Reduces operator fatigue by allowing better tool maneuverability
- Reduces tension put on wrist, hand, elbow and shoulder by the heavy hose
- Free angle fittings rotate 360° and up to 30° of deflection of air tool supply line
- Max working pressure 140 PSI




## TOPRING

Model No	Mfg. No.	Description	Price/Each
TGA770	62.350C	1/4 (M) NPT x 1/4 (M) NPT	
TGA771	62.355C	1/4 (F) NPT x 1/4 (M) NPT	
TGA772	62.360C	1/4 industrial type x 1/4 (M) NPT	
TGA773	62.365C	ARO 210 type x 1/4 (M) NPT	

## HOSE WHIPS

- Easy tool manipulation
- Increases the lifespan of the connector and the main pipe
- Lightweight
- Excellent abrasion resistance



### Application

- Used between the air tool and quick coupler to act as a "shock absorber" and to prolong the life of the coupler

## TOPRING

Model No.	Mfg. No.	Hose I.D."	O.A. Length"	Inlet (M) NPT	Rigid Fitting (F) NPT	Price/Each
TLV350	62.523	1/4	18	1/4	1/4	
TLV351	62.543	3/8	18	1/4	1/4	

## AIR TOOL SWIVEL CONNECTORS

- Improve tool manoeuvrability, minimizes operator's fatigue and extends hose life
- Universal joint that connects portable air tools to an air line
- 360° Swivel at two locations which allows an air hose to drop directly to the floor, no matter how the tool is held

**WARNING:** Not to be used on percussion tools or in areas of high mechanical abuse

### Applications

- For use with most air tools such as:  
Grinders - Sanders - Staple guns - Drills - Buffers - Spray guns - Glue guns
- Maximum working pressure: 150 PSI



## TOPRING

Model No.	Mfg. No.	Port Size NPT	Maximum Air Flow SCFM	Wt. lbs.	Price/Each
UAD500	62.720	1/4	30	0.28	
TA874	62.704C	1/4	33	0.2	
TA876	62.708	1/2	65	0.8	

## SWIVEL CONNECTORS WITH FLOW CONTROL

- Swivels 360° which allows air hose to drop straight to the floor, no matter how the tool is held
- Integrated air-flow control dial
- Maximum working pressure: 150 PSI

**WARNING:** Not to be used on percussion tools or in areas of high mechanical abuse



Model No.	Port Size NPT	Price/Each
THZ360	1/4	



## AIR MANIFOLDS

Eliminates the need to connect and disconnect each time the tool is changed.

### AIR MANIFOLD (3-IN-1)

- Supplies 3 air tools from a single inlet
- Compact design
- Aluminum construction



Model No.	Mfg. No.	Inlet	Outlet	Price/Each
TZ246	62.800C	1/4 (F) NPT	1/4 (F) NPT	
TZ247	62.805C	3/8 (F) NPT	1/4 (F) NPT	

## TOPRING

### AIR MANIFOLD (2-IN-1)

- Supplies 2 air tools from a single inlet
- Compact design
- Nickel brass construction



Model No.	Mfg. No.	Inlet	Outlet	Price/Each
TZ248	62.850C	1/4 (F) NPT	1/4 (F) NPT	
TZ249	62.860C	1/4 (M) NPT	1/4 (F) NPT	

## AIR TOOL SWIVEL CONNECTORS

- Universal connector that connects portable air tools to an air line
- Improve tool maneuverability, minimize operator fatigue and extends hose life
- Swivel 360° at two pivot points, allowing the air hose to drop directly to the floor



## TOPRING

Model No.	Mfg. No.	Thread NPT	Description	Price/Each
TLZ018	62.705C	1/4	Swivel only	

## PNEUMATIC LOCKOUTS

- Prevents fitting from being connected to a pressurized air source
- Stainless steel construction
- Fits virtually all pneumatic fittings in manufacturing facilities

**Model No. TLZ098**

**Mfg. No. S3900**

**Price/Each \$**

**Master Lock**

