<image/>		KEY ACCESSORIE
	<ul> <li>BADGE AND KEY REEL</li> <li>Sidekick offers maximum security for keys and badges</li> <li>Vinyl ID badge strap and split ring for keys</li> <li>Carabiner Diameter: 1-3/8" (3.5 cm)</li> <li>Key Capacity: 5</li> <li>ID Badge Capacity: 1</li> <li>Twist-free end fitting</li> <li>Retraction Force: 0 oz 4 oz.</li> </ul>	<ul> <li>RETRACTORS #6</li> <li>.36° Cord made with DuPont™ Kevlar* fibre</li> <li>.500gh polycarbonate case</li> <li>.6-oz. retraction force</li> <li>.360° rotating clip</li> <li>.1° nickel plated split ring</li> <li>. Holds 10 keys</li> <li>. Belt clip</li> <li>. Ideal for maintenance, janitorial,</li> </ul>
	No. No. Material Length" Type	/Each No. No. /Each
	CHAINS #487-HD • 48" stainless steel cable • Textured chrome front • Stainless steel mounting bracket • S to 10 oz. retraction force • 1 1/8" diameter split ring • Ideal for safety and security personnel	<ul> <li>&amp; KEY REEL WITH WHISTLE</li> <li>Sidekick offers maximum security for keys and badges</li> <li>Vinyl ID badge strap and split ring for keys</li> <li>Carabiner Diameter: 1 3/8" (3.5 cm)</li> <li>Key Capacity: 5</li> <li>ID Badge Capacity: 1</li> <li>FOX40° Classic Safety Whistle</li> <li>Three-chamber pea-less whistle (works wet or dry)</li> </ul>
<image/>	Model Mfg. Price No. No. /Each	With carabiner
Iddel       Mrg.       Price         T2010       4888         PREVENTION OF CONTRACT CARLY PRACE         International control of the control of t	SECURIT <sup>™</sup> KEY-BAK <sup>®</sup> KEY CHAINS • 48" Cord made with DuPont <sup>™</sup> Kevlar <sup>*</sup> fibre • Rugged carabineer makes securing the unit to almost anything easy • Corrosion-proof polycarbonate casing	Model Mfg. Cable Cable
The ORIGINAL KEY-BAK®         • Stainless steel chain extends to 24"         • Pocket watch size         • Chrome true finish         • 1/2 oz. weight         • With regular belt clip         • Retraction Force: 0 oz 4 oz.             Model       Mfg.         • Midel       Mfg.         • Tuzoop       5             • ORIGINAL KEY-BAK®             • Medel       Mfg.         • Midel       Priced         • With regular belt clip       • Constant example         • Retraction Force: 0 oz 4 oz.       • With regular belt clip             • Medel       Mfg.         • Tuzoop       5             • All Social Constant example       • With regular belt clip             • Retraction Force:       • Jain Social Constant example         • Midel       Mfg.         • Midel       Mfg.         • Stain Old Constant example       • With regular belt clip         • Vith regular belt clip       • Midel         • Midel       Mfg.         • Midel       Mfg.         • Stain Old Constant force       • Sin Old Constant force	Model Mfg. Price	OP294 OKBP-0041 Zinc Alloy Metal 24 Kevlar® Cable
No.       No.       // Each         TZ009       5       Image: Stand	TLZ010       488B         THE ORIGINAL KEY-BAK®         • Stainless steel chain extends to 24"         • Pocket watch size         • Chrome texture finish         • 2 1/2 oz. weight         • With regular belt clip	<ul> <li>ID BADGE HOLDERS</li> <li>36" nylon cord</li> <li>Vinyl strap for identification cards (ID)</li> <li>Made of ABS plastic</li> <li>Tested in excess of 180 000 pulls</li> <li>2 oz. retraction force</li> <li>Belt clip</li> <li>Ideal for maintenance and janitorial, safety and security personnel,</li> </ul>
<ul> <li>SELF-RETRACTING REELS #485-HDK.</li> <li></li></ul>	N. N. West	No. No. /Fach
Model Mfg. Price Model Mfg. Price View View Model Mfg. Price View View View View View View View Vie	SELF-RETRACTING REELS #485-HDK • 48" Cord made with DuPont™ Kevlar* fibre • Chrome front • 8 to 10 oz. retraction force • 1 1/8" split ring • Belt clip • Ideal for maintenance, janitorial,	<ul> <li>36" nylon cord</li> <li>Made of ABS plastic</li> <li>3/4" split ring</li> <li>Tested in excess of 180 000 pulls</li> <li>2-oz. retraction force</li> <li>Ideal for maintenance and janitorial, safety and security personnel, identification and communication</li> </ul>
	Model Mfg. Price	Model Mfg. Price