

EARMUFFS

X SERIES EARMUFFS

- The X-Series earmuffs are 3M's latest advancement in hearing conservation
- This low-profile earmuff is designed for protection against low-level industrial noise and other loud sounds
- Earcup pivot points tilt for optimum comfort and efficiency
- Hygiene kit available
- Compatible with WS-CUSH Peltor Wireless Bluetooth Communication accessory

SEJ034



SGC395

3M
PELTOR™

| Model No. | Mfg. No. | Description | CSA Class | NRR dB | Price/Each |
|-----------|----------|--------------------------------|-----------|--------|------------|
| SEJ034 | X1A | Peltor™ X1, Over-Head Headband | A | 22 | |
| SEJ035 | X2A | Peltor™ X2, Over-Head Headband | A | 24 | |
| SEJ036 | X3A | Peltor™ X3, Over-Head Headband | AL | 28 | |
| SEJ037 | X4A | Peltor™ X4, Over-Head Headband | AL | 27 | |
| SEJ038 | X5A | Peltor™ X5, Over-Head Headband | AL | 31 | |
| SGC394 | X1P5E | Peltor™ X1P, Cap Mount | - | 21 | |
| SGC395 | X2P5E | Peltor™ X2P, Cap Mount | - | 24 | |
| SGC396 | X3P5E | Peltor™ X3P, Cap Mount | - | 25 | |
| SGC397 | X4P5E | Peltor™ X4P, Cap Mount | - | 25 | |
| SGC398 | X5P5E | Peltor™ X5P, Cap Mount | - | 31 | |

E-A-RFIT™ DUAL-EAR VALIDATION SYSTEM

- Tests both ears simultaneously in under 5 seconds
- Earmuff and earplug testing capability
- Tests at 7 frequencies, from 125Hz to 8000Hz
- Science-based, objective, quantitative testing



3M

| Model No. | Mfg. No. | Description | Price /Each |
|-----------|------------|--------------------------------------|-------------|
| SDT137 | 393-1100 | E-A-Rfit™ Dual-Ear Validation System | |
| SDT138 | 393-3001-2 | X1/X2 Earmuffs Probed Test Cushions | |
| SDT139 | 393-3003-2 | X3 Earmuffs Probed Test Cushions | |
| SDT140 | 393-3005-2 | X4/X5 Earmuffs Probed Test Cushions | |

TACTICALPRO™ TACTICAL 6 SLIM LINE HEADSET

FOLDING INDUSTRIAL AND PROFESSIONAL SHOOTER ELECTRONIC AMBIENT LISTENING HEADSET

- When clear ambient sound and voice recognition is required in your noisy environment, rely on the latest line of electronic headsets from Peltor®
- Designed with a unique frequency response that amplifies signals, voices and warning sirens while at the same time instantaneously suppressing dangerous impulse noises
- Perfect choice for a wide variety of applications including: gun ranges, forklift drivers, airport ground personnel, maintenance mechanics and hearing-impaired workers
- Hygiene kits available
- Individual cup volume control
- Four AAA batteries for 200 hours of operation
- Colour: Grey



3M
PELTOR™

| Model No. | Mfg. No. | Description | CSA Class | NRR dB | Price/Each |
|-----------|------------------|-------------|-----------|--------|------------|
| SGL202 | MT16H210F-479-SV | Headband | B | 20 | |

PROTAC™ III HEADSET

- Environmental microphones for level-dependent hearing protection and ambient listening
- 3.5 mm listen-only stereo input for connection to external devices (e.g. cell phone, two-way radio, iPod)
- Voice-guided menu system for ease of use and adjusting settings
- Auto power off, the headset will turn off after 4 hrs of non-use to save battery
- Low-battery warning to inform you when to change batteries
- To reduce corrosion caused by sweat and moisture, the electronics are located in a separate compartment of the cup
- Occupational use only
- CSA Class: A



3M
PELTOR™

| Model No. | Mfg. No. | Description | NRR dB | Price /Each |
|-----------|-------------|-------------|--------|-------------|
| SGL200 | MT13H221A | Headband | 26 | |
| SGL199 | MT13H221P3E | Cap Mount | 23 | |
| SGP582 | MT13H221A | Hygiene Kit | - | |

WORKTUNES™ PRO EARMUFFS

- Offers 10 AM/FM presets
- Integrated antenna (no snagging)
- Voice guided menu
- Lightweight
- Uses 3.5 mm jack for audio input
- Provides excellent reception with no interference, even in harsh conditions
- Comfortable for extended use, with soft cushions for low pressure
- 1 year warranty
- CSA Class: A



3M
PELTOR™

| Model No. | Mfg. No. | Description | NRR dB | Price /Each |
|-----------|-------------|-------------|--------|-------------|
| SFV203 | HRXS221A-NA | Headband | 26 | |