

BW™ MAX XT II MULTI-GAS DETECTORS

- Reliably monitors up to four hazards, including H₂S, CO, O₂, and combustibles
- Straightforward one-button operation
- Robust motorized SmartSample pump for intelligent remote sampling, ideal for confined spaces
- Reliable pump block detection; water and other liquids are prevented from being drawn into the pump
- Calibration is required only two times per year with a simple one-button automatic procedure
- Tamper-proof adjustable options can be customized to suit any application
- Built-in rechargeable lithium battery
- Rugged and durable water resistant design with built-in concussion-proof boot
- Standard data logging and event logging
- Fully compatible with the MicroDock II automatic test and calibration system

HX922



Honeywell

| Model No. | Mfg. No. | Description | Price/Each |
|------------------------|-----------------|---|------------|
| HX922 | XT-XWHM-Y-NA | Gas Detector | |
| HX923 | XT-CK-CC | Carrying Case with Foam Insert | |
| CONFINED SPACE KITS | | | |
| HX924 | XT-XWHM-Y-NA-CS | Standard Kit Includes: HX922, IR Connectivity Kit, Regulator, Sampling Probe and Calibration Gas | |
| HX925 | XT-CK-DL | Deluxe Kit Includes: IR Connectivity Kit, Regulator, 10'/3 m Hose, Sampling Probe and Auxiliary Filter (Detector and Calibration Gas Sold Separately) | |
| POWER OPTIONS & SPARES | | | |
| HX926 | XT-C01-MC5 | Five Unit Cradle Charger | |
| HX905 | GA-PA-1-MC5 | Five Unit Power Adaptor | |
| HX906 | GA-VPA-1 | 12-24 VDC Vehicle Power Adaptor | |
| HX907 | GA-PA-3 | 12-24 VDC Direct-Wire Power Adaptor | |

BW CLIP REAL TIME SINGLE-GAS DETECTORS

- Real-time gas level display with the ability to calibrate the device
- Maintenance-free: no sensor or battery changes necessary
- Offers extended longevity with a field-replaceable battery and sensor
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Hibernation mode with case accessory or IntelliDoX
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 35 most recent gas events and bump test results
- Compatible with MicroDock II and Fleet Manager II software
- Affordable, with low cost of ownership
- BW recommends performing a bump test prior to each day's use to confirm sensor response and alarm



Honeywell

| Model No. | Mfg. No. | Hazard | Measuring Range | Default Alarm Setpoints Low | High | Price /Each |
|------------------------------------|--------------|-------------------------------------|-----------------|-----------------------------|------------|-------------|
| BW CLIP REAL TIME 2-YEAR DETECTORS | | | | | | |
| HZ270 | BWC2R-H | Hydrogen sulfide (H ₂ S) | 0-100 ppm | 10 ppm | 20 ppm | |
| HZ271 | BWC2R-H510 | Hydrogen sulfide (H ₂ S) | 0-100 ppm | 5 ppm | 20 ppm | |
| HZ273 | BWC2R-M | Carbon monoxide (CO) | 0-300 ppm | 35 ppm | 200 ppm | |
| HZ274 | BWC2R-M50200 | Carbon monoxide (CO) | 0-300 ppm | 50 ppm | 200 ppm | |
| HZ275 | BWC2R-X | Oxygen (O ₂) | 0-25% | 19.5% vol. | 23.5% vol. | |
| HZ276 | BWC2R-S | Sulfur Dioxide (SO ₂) | 0-100 ppm | 5 ppm | 20 ppm | |
| HZ277 | BWC2R-S24 | Sulfur Dioxide (SO ₂) | 0-100 ppm | 2 ppm | 20 ppm | |
| BW CLIP REAL TIME 3-YEAR DETECTORS | | | | | | |
| HZ278 | BWC3R-H | Hydrogen sulfide (H ₂ S) | 0-100 ppm | 10 ppm | 20 ppm | |
| HZ279 | BWC3R-M | Carbon monoxide (CO) | 0-300 ppm | 35 ppm | 200 ppm | |

BW CLIP 4 MULTI-GAS DETECTORS

- Alarm Setpoints: 5-10 ppm
- Maintenance-free: no sensor or battery changes necessary
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 70 most recent gas events and bump test results
- IntelliDoX compatible
- Affordable, with low cost of ownership



HZ284



HZ285

Honeywell

| Model No. | Mfg. No. | Hazard | Colour | Price /Each |
|-----------|----------|---|--------|-------------|
| HZ284 | BWC4-B-N | O ₂ , H ₂ S, CO/LEL | Black | |
| HZ285 | BWC4-Y-N | O ₂ , H ₂ S, CO/LEL | Yellow | |

BW CLIP SINGLE-GAS DETECTORS

- Maintenance-free: no sensor or battery changes necessary
- Offers extended longevity with a field-replaceable battery and sensor
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Hibernation mode with case accessory or IntelliDoX
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 35 most recent gas events and bump test results
- Compatible with MicroDock II and Fleet Manager II software
- Affordable, with low cost of ownership
- BW recommends performing a bump test prior to each day's use to confirm sensor response and alarm
- Note: Monitors do not have a continuous display of the gas concentration, the concentration of the gas will only be displayed when an alarm point is reached



Honeywell

| Model No. | Mfg. No. | Hazard | Measuring Range | Default Alarm Setpoints Low | High | Price /Each |
|--------------------------|-------------|-------------------------------------|-----------------|-----------------------------|------------|-------------|
| BW CLIP 2-YEAR DETECTORS | | | | | | |
| HZ174 | BWC2-H | Hydrogen sulfide (H ₂ S) | 1-100 ppm | 10 ppm | 15 ppm | |
| HZ175 | BWC2-H510 | Hydrogen sulfide (H ₂ S) | 1-100 ppm | 5 ppm | 10 ppm | |
| HZ176 | BWC2-H515 | Hydrogen sulfide (H ₂ S) | 1-100 ppm | 5 ppm | 15 ppm | |
| HZ177 | BWC2-M | Carbon monoxide (CO) | 0-300 ppm | 35 ppm | 200 ppm | |
| HZ178 | BWC2-M50200 | Carbon monoxide (CO) | 0-300 ppm | 50 ppm | 200 ppm | |
| HZ181 | BWC2-X | Oxygen (O ₂) | 0-25% | 19.5% vol. | 23.5% vol. | |
| HZ179 | BWC2-S | Sulfur Dioxide (SO ₂) | 0-100 ppm | 5 ppm | 10 ppm | |
| HZ180 | BWC2-S24 | Sulfur Dioxide (SO ₂) | 0-100 ppm | 2 ppm | 4 ppm | |
| BW CLIP 3-YEAR DETECTORS | | | | | | |
| HZ183 | BWC3-H | Hydrogen sulfide (H ₂ S) | 0-100 ppm | 10 ppm | 15 ppm | |
| HZ184 | BWC3-M | Carbon monoxide (CO) | 0-300 ppm | 35 ppm | 200 ppm | |

ACCESSORIES

| Model No. | Mfg. No. | Description | Qty /Pkg | Price /Each |
|-----------|-----------------|------------------------------|----------|-------------|
| HZ185 | CLIPHB-CASE | Hibernation Case for BW Clip | 1 | |
| HZ186 | CLIPHB-CASE-B50 | Hibernation Case for BW Clip | 50 | |