

## EVOTECH® ARC FLASH HARNESSSES

- Reflectivity on shoulder padding provides increased visibility in low-light applications
- Moisture-wicking padding keeps users cool
- 100% Kevlar webbing is fire-resistant and self-extinguishing
- Lighter than comparable harnesses
- Padded shoulders
- Weight Capacity: 400 lbs.
- Chest Strap Connections: Quick-Connect



Model No.	Mfg. No.	D-Rings	Leg Strap Connections	Size	CSA Class	Price /Each
SGE629	10150156	Back	Pass-Through	Universal	A	
SGE630	10150144	Back	Quick-Connect	Universal	A	
SGE631	10150145	Back	Quick-Connect	X-Large	A	
SGE632	10155824	Back/Side	Pass-Through	Universal	A,P	
SGE633	10150152	Back/Side	Quick-Connect	Universal	A,P	
SGE634	10150153	Back/Side	Quick-Connect	X-Large	A,P	

SGE629



## V-FLEX® FULL-BODY SAFETY HARNESS

- Using a patent-pending RaceFLEX connection, webbing is routed across the chest for a secure and comfortable fit—eliminating the need for bulky chest straps or cumbersome buckles
- Reduce fatigue with flexible foam shoulder pad that responds to your movement to conform to your body, eliminating pressure points and chafing
- Keep cool and reduce heat stress with interior padding designed with channels for continuous air flow and ventilation
- Using an exclusive racing style design, webbing contours to the torso, reducing the need for adjustments throughout the day and allowing for better mobility on the job
- Featuring a patent-pending hip connection, the harness "flexes" with the worker, reducing fatigue throughout the day
- Pull down adjustment allows you to quickly and easily get the right fit that last throughout the work day
- Closed cell foam reduces moisture build-up – keeping your pad from getting soggy and extending the life of your harness
- Vented "V" feature allows for fresh air to flow from outside the pad, to inside
- Type: Fall Arrest • CSA Class: A
- D-Rings: Back
- Chest Strap Connections: Quick-Connect
- Standard(s) Met: ANSI Z359.11, CSA Z259.5, OSHA

SGH484



## GRAVITY® WELDER HARNESSSES

- Made of 100% Kevlar webbing
- Performs very well in high heat and welding applications
- CSA Class: A
- Weight Capacity: 400 lbs.
- D-Rings: Back
- Leg Strap Connections: Pass-Through
- Chest Strap Connections: Pass-Through

SGE639



Model No.	Mfg. No.	Weight Capacity	Size	Leg Strap Connections	Price /Each
SHG485	10239822	150 lbs.	X-Small	Quick-Connect	
SHG484	10239740	230 lbs.	Regular	Quick-Connect	
SHG486	10239981	300 lbs.	X-Large	Quick-Connect	
SHG487	10239982	400 lbs.	2X-Large	Quick-Connect	
SHG488	10239983	150 lbs.	X-Small	Tongue Buckle	
SHG489	10239984	230 lbs.	Regular	Tongue Buckle	
SHG490	10239985	300 lbs.	X-Large	Tongue Buckle	
SHG491	10239986	400 lbs.	2X-Large	Tongue Buckle	



Model No.	Mfg. No.	Size	Price /Each
SGE639	10103216	Universal	
SGE640	10103217	X-Large	

## GRAVITY® FULL BODY SUSPENSION HARNESS

- Premium hardware fittings with wide opening aluminum D-rings, triple action carabiner, and single hand adjusting buckles
- Five rigid tool loops on the waist belt and leg connections
- Bayonet buckles with locking engagement window confirms a secure connection
- Strategically positioned ventral attachment distributes the load between the waist belt and leg loops during suspension
- Breathable waist pad is constructed from a multi-layered padding which dissipates pressure from the webbing to reduce fatigue when working for long periods of time
- Rolled-edge shoulder padding protects the neck from chafing while providing the necessary back support
- Type: Descent Control, Evacuation/Retrieval, Fall Arrest, Ladder Climbing, Work Positioning
- CSA Class: ADEL P
- Weight Capacity: 400 lbs.
- D-Rings: Back - Front - Shoulder - Side
- Leg Strap Connections: Quick-Connect
- Chest Strap Connections: None
- Colour: Green

SGT225



Model No.	Mfg. No.	Size	Price /Each
SGT225	10150453	Small	
SGT226	10150454	Medium	
SGT227	10150455	Large	

