

SEAL TIGHT™ BALL VALVE LOCKOUTS

- Compact, lightweight, flexible and easy to use, the Seal Tight™ valve lockout works on virtually every valve size and applications
- Eliminates the risk of accidentally moving a handle by removing it and concealing the stem
- Effectively locks out all valves from 3/8" to 4", thus eliminating specific valve lockout systems
- Simple to apply, with an intuitive wrapping strap and locking mechanism
- Works on virtually all valves; metal and PVC, insulated pipes, ceiling or wall-mounted pipes and hard to reach valves
- Made of PVC polyester fabric and HDPE plastic, it withstands corrosive environments and operates in temperatures from -40°F to 300°F

Model No. SAO596
Mfg. No. 468L
Price/Each \$

**Master
Lock**



ELECTRICAL LOCKOUT OVERSIZED PLUG AND HOIST CONTROL COVER

- Offers broad application solutions sized at 7" diameter by 17" tall
- Insert PVC tubing to block access to control buttons for hoist control lockout
- Flexible and durable rip-stop nylon bag fits easily in safety tool boxes
- Lock out with up to six padlocks or hasps
- Trilingual lock out warning printed on bag

Model No. SAO706
Mfg. No. 453L
Price/Each \$



**Master
Lock**

BLIND FLANGE LOCKOUT DEVICE

- Cover and lock out nuts ranging from 3/4" to 1-1/8" diameter
- Adjustable device provides a tight fit, adapting to multiple flanged pipe applications
- Device fully conceals flange bolts preventing access to the blind until all work has been completed
- Four locking holes allow for multiple workers to lockout device at one time
- Durable aluminum and hardened steel construction withstands conditions indoors and out



**Master
Lock**

Model No.	Mfg. No.	Size	Pipe Diameter Range	Nut Diameter	Flange Width Range	Price /Each
SDS646	S3922	Small	1/2" – 3" (12.7 mm – 76.2 mm)	1-1/8" (19 mm – 28.7 mm)	1-1/2" – 5-5/8" (38.1 mm – 143.3 mm)	
SDS647	S3923	Medium	3-1/2" – 12" (88.9 mm – 304.8 mm)	1" – 1-7/8" (33.3 mm – 47.8 mm)	3-3/4" – 10-3/4" (95.3 mm – 274.6 mm)	
SDS648	S3924	Large	14" – 24" (355.6 mm – 609.6 mm)	2" – 2-3/4" (52.3 mm – 69.9 mm)	7-3/4" – 17-7/8" (196.9 mm – 447.8 mm)	

ROTATING GATE VALVE LOCKOUTS

- Outward/inward rotation allows for easier installation and storage
- Unique, patent-pending outward rotation allows for easier installation in confined space applications
- Surrounds the valve operating handle, protects against accidental valve opening
- Each size rotates into itself to fit effectively into safety tool boxes
- Each size nests within the next larger size to save space in storage
- Tough, lightweight, dielectric Zenex™ thermoplastic bodies withstand chemicals; perform effectively in extreme conditions (temperature range -50°F (-46°C) to 350°F (177°C))
- Up to four workers can apply their personal safety locks
- Red lockout colour identifies the safety lockout application
- Complete with high-visibility permanent safety labels (English, French and Spanish) that can be written on to identify the responsible person and then erased for the next job



SAL529



SAL528



SAL531

**Master
Lock**

Model No.	Mfg. No.	Description	Price /Each
SAL526	480	Fits 1" to 3" Dia. Valve Handle	
SAL527	481	Fits 2" to 5" Dia. Valve Handle	
SAL528	482	Fits 4" to 6 1/2" Dia. Valve Handle	
SAL529	483	Fits 6" to 10" Dia. Valve Handle	
SAL530	484	Fits 8" to 13" Dia. Valve Handle	
SAL531	485	1 Set Consists of 1 x SAL526, SAL527, SAL528, SAL529 & SAL530	