

## SDS PLUS ROTARY HAMMER KITS

- Thin Wall Core Bit Capacity: 3"
- Vibration: 10.6 m/s<sup>2</sup>
- Drilling mode: 3-mode: Rotary hammer, hammer only, rotation only
- Get up to 85% faster drilling and 85% harder hitting while reducing vibration
- Equipped with an all metal gear case and mechanical clutch to provide maximum durability
- Powerful and lightweight
- Kit includes a side handle, depth rod and carrying case

**Model No. TYO341**  
**Mfg. No. 5268-21**  
**Price/Each \$**

### SPECIFICATIONS

**Solid Bit Capacity:** 1 1/8"  
**Amperage:** 8.0  
**No Load RPM:** 0-1500  
**No Load BPM:** 0-5500  
**Impact Energy:** 3.6 ft.-lbs.  
**Tool Weight:** 7.5 lbs.



## SDS MAX ROTARY HAMMERS

- Thin wall core bit capacity: 4"
- Drilling mode: 2-mode: Rotary hammer and hammer only
- Heavy-duty 5.5 ft.-lbs. of impact energy for solid performance
- Constant Power Technology ensures consistent drilling power for the toughest applications
- A 12-position chipping adjustment lets you maintain the optimum hammer position while chipping in any orientation
- A mechanical clutch protects the motor when the bit binds
- Two-mode operation offers maximum versatility regardless of the application
- Tool comes with a side handle and carrying case

**Model No. TMB675**  
**Mfg. No. 5317-21**  
**Price/Each \$**

### SPECIFICATIONS

**Solid Bit Capacity:** 1 9/16"  
**Amperage:** 10.5  
**No Load RPM:** 0-450  
**No Load BPM:** 0-3000  
**Impact Energy:** 5.5 ft.-lbs.  
**Tool Weight:** 15 lbs.



## L-SHAPE SDS PLUS ROTARY HAMMER

- Wide optimal drilling range for a single-hammer solution
- SHOCKS Active Vibration Control® technology reduces vibration felt at the handles for less user fatigue and greater productivity
- Factory-set clutch reduces sudden, high-torque reactions if bit jams
- Variable speed trigger for accurate hole starting
- Optimized ergonomic design provides excellent control in all orientations
- OSHA Table 1 Compliant dust extraction compatible
- Includes: Rotary Hammer D25333, Kit Box

**Model No. UAD826**  
**Mfg. No. D25333K**  
**Price/Each \$**

### SPECIFICATIONS

**Bit Capacity:** 3/16" - 7/8"  
**Amps:** 8.5 A  
**No Load BPM:** 0-5200 BPM  
**No Load RPM:** 0-1150 RPM  
**Impact Energy:** 2.58 ft.-lbs.  
**Power Tool Type:** Corded  
**Tool Weight:** 8.16 lbs.



## 7/8" SDS PLUS ROTARY HAMMER KIT

- Three modes of operation: Rotary hammer, hammer only and rotation only
- Mechanical clutch: Protects the motor when the bit binds
- Variable position chisel stop: Allows material to be adjusted, regardless of orientation
- Includes: (1) Carrying case, (1) depth rod, (1) side handle

**Model No. TLV204**  
**Mfg. No. 5263-21**  
**Price/Each \$**

### SPECIFICATIONS

**Solid Bit Capacity:** 7/8"  
**Amperage:** 7.0  
**No Load RPM:** 0-1500  
**No Load BPM:** 0-5625  
**Impact Energy:** 1.8 ft.-lbs.  
**Tool Weight:** 5.8 lbs.



## 5/8" SDS+ ROTARY HAMMERS

- Lightweight, 4.6 lbs, compact, 10 1/4" length: Allows for work in tight spaces
- Mechanical clutch: Protects tool when bit binds up
- AVS - Anti vibration system: Delivers maximum comfort by minimizing vibration
- 2-mode operation: Rotary hammer and rotation only for maximum versatility
- Includes: Side handle, depth rod and carrying case

**Model No. TLV203**  
**Mfg. No. 5263-21**  
**Price/Each \$**

### SPECIFICATIONS

**Solid Bit Capacity:** 5/8"  
**Amperage:** 5.5  
**No Load RPM:** 0-3700  
**No Load BPM:** 0-4400  
**Impact Energy:** 1.5 ft.-lbs.



## DEMOLITION HAMMERS W/ANTI-VIBRATION

- Anti-Vibration Technology enabled to reduce fatigue and injury due to exposure to vibration
- Extra long auto cut off carbon brushes provides reduced maintenance
- Electronic speed and variable control gives efficient hammering at the desired speed
- Includes: Side handle, bull point and carrying case

**Model No. TLY750**  
**Mfg. No. HM1214C**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 14.0  
**BPM:** 950-1900  
**Impact Energy:** 18.95 ft.-lbs.  
**Tool Weight:** 27.1 lbs.



## PAVEMENT BREAKERS

- Active Vibration Control reduces user fatigue and increases comfort and productivity
- Electronic soft start increases productivity by reducing bit walking
- Rubber coated handles provide greater comfort and control

**Model No. TLY751**  
**Mfg. No. D25980**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 15.0  
**BPM:** 900  
**Impact Energy:** 61 ft.-lbs.  
**Tool Weight:** 68.3 lbs.

