

3/8" IMPACT WRENCHES

For general maintenance

- Twin hammer clutch
- Composite handle and magnesium clutch housing
- S2S technology allows to effortless change between forward and reverse
- Three positive power settings
- Full teasing trigger

Model No. TLV696



3/8" BUTTERFLY IMPACT WRENCHES

- Butterfly forward/reverse throttle
- Rocking dog clutch for smooth operations and durability
- Four positive power settings
- Easy maneuvering with 360° air inlet swivel
- Comfort and maneuverability
- Shank size: 3/8"
- Shank retainer type: Friction ring
- Working torque: 5-65 ft-lbs.
- Ideal for bench work, carburetors, ignitions, body panels, transmissions, oil pans and small engine repair

Model No. THZ806



1/2" IMPACT WRENCHES

For general duty repair/maintenance and light-to-medium assembly applications.

- Twin clutch increases ultimate torque for smooth operation under heavy loading
- Oil bath clutch
- Teasing throttle

Model No. THZ948



1/2" IMPACT WRENCHES

Standard duty for use in a variety of fastening operations.

- Dyna Pact™ clutch
- Built-in power regulator
- Push-through reverse mechanism

Model No. THZ946



1" IMPACT WRENCHES

Standard duty for use in steel erection, heavy assembly/disassembly, maintenance/repair, and construction.

- Teasing throttle
- Rocking dog clutch
- Closed-grip inside trigger
- 6" extended shank
- 1/2" (NPTF) air inlet thread
- 1/2" min. hose size

Model No. TJZ370



3/4" IMPACT WRENCHES

High ultimate torque for tough applications.

- Ideal for hard pull up conditions
- Push-through reverse mechanism
- Teasing throttle
- Oil bath clutch chamber
- Pin clutch
- 3/8" (NPTF) air inlet thread
- 3/8" min. hose size

Model No. THZ955



Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

Standard equipment: removable dead handle. **TG063**: Socket pin and retaining ring. **TG065**: adjustable and removable dead handle, socket pin and retaining ring.