

## 1.6 CONTINUOUS HP, 4.5-GALLON ELECTRIC WHEELED PORTABLE COMPRESSORS

- Vertical stand feature allows a user to transport or store compressor in a vertical position
- 78 dBA (tested per ISO3477) operational noise level for a quieter work environment
- 10" non-flat foam tires allow for easy transportation around the jobsite
- Oil free, maintenance free pump, for convenient use
- High flow coupler allows for maximum nailer performance
- Metal console panel provides gauges, couplers and regulators

**Model No. TLV990 Mfg. No. D55146**  
**Price/Each \$**

**Horsepower:** 1.6 HP  
**Tank Size:** 4.5 Gal  
**Power Supply:** 120V  
**CFM @ 100 PSI:** 5.2  
**Max PSI:** 175  
**Dimensions:** 33.5" L x 23" W x 15" H  
**Weight:** 83 lbs.



## 0.3 CONTINUOUS HP 1-GALLON SINGLE TANK HAND CARRY COMPRESSORS

- 0.75 SCFM delivered @ 90 PSI pump, 1.0 gallon tank and 135 max PSI enables more nails to be fired and provides quicker recovery
- Durable oil-free pump provides extended maintenance-free operation
- Low 71 dBA\* allows for quieter operation (\*Tested per ISO3744)
- Roll cage and control panel provide protection to key compressor components
- Low 2.6 amp draw motor provides easy start-up and reduces breaker tripping
- Ball valve drain allows for quick and thorough tank draining
- One quick coupler to easily support 1 nailer
- High-flow regulator for increased performance

**Model No. TJZ977 Mfg. No. D55140**  
**Price/Each \$**

**Drive:** Belt drive  
**Horsepower:** 0.3 continuous HP  
**Tank Size:** 1.0 gal.  
**Power Supply:** 120 V, 10 A, 60 Hz, universal motor  
**CFM @90 PSI:** 0.75 CFM  
**Pump Speed:** 2200 RPM  
**Dimensions:** 19" L x 14.5" W x 9" H  
**Weight:** 29 lbs.



## CONTINUOUS WHEELED AIR COMPRESSOR

- Cast iron cylinder enhances pump life
- High-flow regulator for increased performance
- Oil lubricated pump improves durability
- Dual soft start valves assist in cold weather start-up
- Top load panel with positioning holes allows unit to transport loads up to 100 lbs
- Run multiple tools from dual universal quick couplers
- Ball valve drain allows for quick and thorough tank draining
- Features 10" pneumatic wheels and handle for ease of mobility
- Electric/Gas: Electric
- CFM: 5 at 100 PSI



Model No.	Mfg. No.	Horse Power	Voltage /Phase	Tank Capacity	Max. PSI	Sound Level (dBA)	Pump Speed	Height"	Length"	Width"	Weight lbs.	Wheel Diameter"	Price /Each
TLV989	D55168	1.6HP	120/1	15 Gal. (18 US Gal)	225	78	1750 RPM	44-3/4	24-1/2	22	92	2	

## PORTABLE CONTRACTOR SERIES COMPRESSORS – OIL LUBE, DIRECT DRIVE

- For professional, farm, home and hobbyists
- Quiet running and low 1720 RPM pump
- Die cast aluminum pump with cast iron sleeves and stainless steel valves for longer life
- All electrical units draw 15 amps or under
- Manual reset for overload protection
- Includes: Regulator, pressure gauge, pressure switch with on/off, universal coupler, filter silencer with replacement element and pump oil
- Air outlet accepts 1/4" industrial male quick connector
- Factory tested prior to shipment
- Not intended for commercial use
- CSA approved
- 1-year limited manufacturer's warranty

TFA008



TFA009



TFA010



Model No.	Mfg. No.	Peak HP	Running HP @ 90 PSI	Actual FAD-CFM		Voltage /Phase	Amp Draw @ 125 PSI	Tank Size (gal.)	Pump RPM	Dimensions			Wt. lbs.	Price /Each	
				90 PSI	125 PSI					L"	W"	H"			
TFA008	DD-1004	1	1	4.5	4	115 V/1 PH	15	4	1720	16	x	16	x	23	65
TFA009	DD-1503	1.5	1.5	6	4.6	115 V/1 PH	14	3.2	1720	22	x	9	x	23	55
TFA010	DD-2022B	2	1.5	6	4.6	115 V/1 PH	15	4	1720	21	x	20	x	20	80