

## ZINC-100™ BRIGHT GALVANIZING SPRAY

- Bright galvanizing spray provides long-lasting corrosion protection
- Specially formulated for the touch-up and repair of hot galvanized parts
- Zinc flakes permanently bond to metallic surfaces
- Bright metallic finish matches hot dipped look
- Fast drying
- Zinc-rich formula meets ASTM A780 standard
- For use on ferrous metals and steel
- Suitable for touch-up, repair, manufacturing or installation of food processing equipment, water storage tanks, fencing, outside structures, playground and sports equipment, scaffolding, ducting and air conditioning systems, marine equipment, architectural and ornamental structures, and steel components



Model No.	Mfg. No.	Size	Price /Each
AA196	53H102	400 ml	

## ZINC-200™ COLD GALVANIZING SPRAY

- High-performance, fast-drying corrosion protection spray specially formulated for ferrous metals
- Actively fights rust and corrosion
- Dual-action protection with its resin coat and galvanic action
- 95% pure zinc
- Dull finish and dries to touch in 3-5 minutes
- Meets ASTM A780 & MIL specifications
- Applications include manufacturing, repair, and installation of fencing, outside structures, playground and sports equipment, scaffolding, ducting and air conditioning systems, marine equipment, and architectural and ornamental structures



Model No.	Mfg. No.	Size	Price /Each
AB646	53H152	400 ml	

## THERMAPLEX® MULTI-PURPOSE BEARING GREASE

- Excellent load carrying properties
- Prolongs bearing life
- Ideal for lubricating all types of bearings
- Blue coloured paste
- Petroleum odour
- Temperature range: -22°F (-30°C) to 350°F (177°C)
- Dropping point: 429°F (220°C)
- NLGI Grade: No. 2
- Lithium complex



Model No.	Mfg. No.	Size	Price /Each
AA847	C70614	400 g	

## THERMAPLEX® AQUA BEARING GREASE

- Resists water washout
- Excellent corrosion resistance
- Significant load carrying capability
- Greater degree of bearing protection
- Amber coloured paste
- Petroleum odour
- Temperature range: -4°F (-20°C) to 302°F (150°C)
- Dropping point: 500°F (260°C)
- NLGI Grade: No. 2
- Aluminum complex



Model No.	Mfg. No.	Size	Price /Each
AA851	C70514	400 g	

## THERMAPLEX® HI-LOAD BEARING GREASE

- Withstands shock loading
- Reduces wear from vibration
- Excellent anti-wear properties
- Wide operating temperature range
- Blue/black colour paste
- Lithium complex
- Petroleum odour
- Moly-fortified for extreme applications to 350°F (177°C)
- Dropping point: 429°F (220°C)
- NLGI Grade: No. 2



Model No.	Mfg. No.	Size	Price /Each
AA850	C70414	400 g	

## THERMAPLEX® FOODLUBE BEARING GREASE

- Metal & X-ray detectable plastic component
- Ensures safety in areas where incidental food contact may occur
- Does not contain, solvents or silicone
- Non-staining and non-emulsifying
- White coloured paste
- Mild odour
- Aluminum complex
- Temperature range: -4°F (-20°C) to 302°F (150°C)
- Dropping point: 500°F (260°C)
- NLGI Grade: No. 2
- Made of FDA compliant materials
- NSF registered category code H1
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AA852	C70114	400 g	

## THERMAPLEX® HI-TEMP BEARING GREASE

- Resists carbonization at high temperatures
- Extends relubrication intervals
- Reduces risk of bearing failure at high temperature
- Ensures optimal production rates
- Smooth, brown paste
- Petroleum odour
- Lithium complex
- Temperature range: -15°F (-26°C) to 392°F (200°C)
- Dropping point: 536°F (280°C)
- NLGI Grade: No. 2



Model No.	Mfg. No.	Size	Price /Each
AA848	C70214	400 g	

## THERMAPLEX® CS MOLY BEARING GREASE

- Excellent oxidation stability, adhesive and cohesive properties and corrosion resistance
- Exceptional water resistance
- Premium performance
- Calcium sulfonate grease
- Contains molybdenum disulfide
- Reduces wear from vibration
- High load carrying capacity
- Prolongs bearing life
- Wide operating temperature range: 0°F to 425°F (-18°C to 218°C)
- Extends re-lubrication intervals for bearings
- NLGI No. 2
- NSF registered category code H2



Model No.	Mfg. No.	Size	Price /Each
AD179	C70814	400 g	

## PISTOL GREASE GUNS

### HEAVY-DUTY

- Designed for use in general confined spaces or where access to grease nipples is restricted
- Heavy-duty die cast grease gun head
- Develops 5000 PSI
- Capacity: 14 oz (400 g) grease cartridge or suction fill
- AC475 comes complete with 4" steel extension and 4-jaw coupler with ball check
- AC476 comes complete with 18" flexible hose and 4-jaw coupler with ball check

Model No. AC475  
Price/Each \$  
Model No. AC476  
Price/Each \$



**AURORA**  
TOOLS