



DATA LOGGING INDOOR AIR QUALITY METER WITH HUMIDITY CALIBRATION STANDARDS

- Includes: R9905 Data Logging Indoor Air Quality Meter, R9933 33% Humidity Calibration Standard, R9975 75% Humidity Calibration Standard
- Measures carbon dioxide (CO₂), temperature, humidity and automatically calculates time-weighted average (TWA) and short-term exposure Limit (STEL)
- CO₂ Range: 0 - 30000 ppm
- Temperature Range: -4° - 140° F (-20° - 60° C)
- Humidity Range: 0% - 100% RH



REED

Model No.	Mfg. No.	Description	Price/Each
IC861	R9905-KIT	Indoor Air Quality Meter	

INDOOR AIR QUALITY METER WITH DESKTOP/WALL MOUNT

- Measures and records carbon dioxide (CO₂), temperature, and humidity
- Features a high-resolution color TFT touchscreen display, user-selectable recording times, programmable alarm set points, a built-in desk stand, and a wall mounting bracket
- Quickly generate an Excel file with raw data and export recorded data to a computer without the use of the software
- Low-drift NDIR CO₂ sensor for stable and accurate readings
- Max/min display
- Internal 16GB memory stores data points in CSV format
- User selectable sampling rate from 1 second to 24 hours
- Internal time and date stamp
- Rechargeable li-ion battery
- Low battery indicator
- Includes: Indoor air quality meter, USB cable, Power Adapter, Wall mounting bracket
- CO₂ Range: 0 - 9999 ppm
- Temperature Range: 32° - 122° F (0° - 50° C)
- Humidity Range: 0% - 100% RH
- Manufacturer's Warranty: 1 Year



REED

Model No.	Mfg. No.	Description	Price/Each
IC868	R9920	Indoor Air Quality Meter	
IC869	R9920-NIST	Indoor Air Quality Meter with ISO Certificate	

REFRACTOMETER

- This 0 to 55% Brix digital handheld refractometer measures the concentration percentage in almost any juice, drink, or food, such as soup, sauce, or jams
- Features a fast three-second response time and a dual LCD, which simultaneously shows % Brix and temperature
- Ergonomically designed for one-handed operation
- Features built-in ATC (Automatic Temperature Compensation), single Zero calibration, a prism cover, rechargeable Li-ion battery, and an IP54-rated housing
- Sapphire prism with abrasion and corrosion-resistant coating
- Includes: Digital refractometer, USB cable, Cleaning cloth, Solution/sample applicator
- Temperature Range: 50 to 104°F (10 to 40°C)



REED

Model No.	Mfg. No.	BRIX Range	BRIX Resolution	Price/Each
IC867	R9510	0 - 55 %	0.1 %	

CONDUCTIVITY/TDS/SALINITY METERS

- Displays both temperature and conductivity, total dissolved solids (TDS), or salt levels simultaneously on a dual LCD display
- Automatic Temperature Compensation (ATC)
- Data hold and Min/Max functions
- User selectable °F or °C
- Waterproof housing meets IP57 standard
- Replaceable electrode module
- Low battery indicator and auto shut off
- (4) AAA batteries power supply
- CE & IP57 certified
- Measurement Range: 0 - 2000 µS, 2 mS/cm - 20 mS/cm
- Salinity Measuring Range: 0 to 1000ppm, 1 to 12ppt
- Total Dissolved Solids (TDS) Measuring Range: 0 to 1300ppm, 1.30 to 13ppt
- Temperature Measuring Range: 32 to 194°F (0 to 90°C)
- Manufacturer's Warranty: 1 Year
- Includes: (1) R3530 Conductivity/TDS/Salinity Meter, (4) Batteries, (1) Hard Carrying Case, (1) Allen Key, (2) Replacement Screws, (1) Lanyard



IC873

REED

Model No.	Mfg. No.	Description	Price/Each
IC873	R3530	Conductivity/TDS/Salinity Meter	
IC874	R3530-NIST	Conductivity/TDS/Salinity Meter with ISO Certificate	
IC879	R3530-KIT	Conductivity/TDS/Salinity Meter with Solution	

PH/MV METERS WITH TEMPERATURE

- Measures pH and mV levels in liquids
- Microprocessor provides automatic buffer solution recognition
- Dual LCD displays pH or mV and temperature simultaneously
- Automatic Temperature Compensation (ATC)
- Designed for handheld or wall mount applications
- User selectable °F or °C
- Replaceable electrode module
- Low battery indicator and auto shut off
- 9 V battery or optional AC adapter power supply
- CE certified
- pH Range: 0 - 14 pH
- Operating Temperature: 32 to 122°F (0 to 50°C)
- Includes: pH/mV Meter, pH Electrode, protective holster, 4 and 7pH Buffer Solution, mounting suction cup, battery
- Manufacturer's Warranty: 1 Year



IC871

REED

Model No.	Mfg. No.	Description	Price/Each
IC871	R3525	pH/mV Meter	
IC872	R3525-NIST	pH/mV Meter & ISO Certificate	
IC875	R3525-KIT	pH/mV Meter with Buffer Solution	
IC876	R3525-KIT2	pH/mV Meter with Buffer Solution & Power Adapter	